

Transchem Pro Inc. PO BOX 1669 Bolingbrook, Illinois 60440

Material Safety Data Sheet

EMERGENCY SPILL PHONE: 1 (800) 535-5053 (INFOTRAC) MSDS No: HP-640

EMERGENCY MEDICAL PHONE: Contact Your Local Poison Control Center

PRODUCT INFORMATION PHONE: 1 (877) 857-3870

NFPA Hazard Ratings: Health 2, Flammability 0, Reactivity 0

HMIS Hazard Ratings: Health 2, Flammability 0, Reactivity 0, Protection B

Prepared By: Technical Group, Phone: 1 (877) 857-3870

Date Issued: March 01, 2014

1- MATERIAL IDENTIFICATION

PRODUCT NAME: LOW pH FRICTIONLESS PRE-SOAK, HP-640

Chemical Family: Surfactant Solution, Additives
Material Use or Occurrence: Frictionless Pre-Soak

2- IMPORTANT INGREDIENTS

CHEMICAL NAME	CAS No.	PERCENT	PEL/TLV/TWA		CARCINOGEN
(Synonyms)			<u>OSHA</u>	<u>ACGIH</u>	(OSHA,NPT,IARC)
Water	7732-18-5	59-79%	N/A	N/A	No
Phosphoric Acid	7664-38-2	7-12%	1 mg/m ³	1 mg/m ³ TWA; 3 mg/m ³ , S	TEL No
Ethylene Glycol Butyl Ether	111-76-2	5-10%	25ppm	25ppm	No
(Butyl Cellosolve)			(Skin)	(Skin)	
Alcohol ethoxylate	68439-46-3	7-13%	N/A	N/A	No

3- CHEMICAL AND PHYSICAL PROPERTIES

Boiling Point: n/av

Specific Gravity: 1.05 g/cc

Solubility In Water: Complete

Evaporation Rate: Similar to water

Solubility In Water: Complete

Solubility In Water: Similar to water

Whon-volatile: 15-30%

Coefficient of Oil/Water Distribution: n/av pH: 1.0- 2.5 Appearance: Clear liquid Odor: Mild

4- FIRE AND EXPLOSION DATA

Flash Point (Seta Flash Cl. Cup): N/A Explosive Limits: Lower: n/ av Upper: n/ av

Extinguishing Media: Treat as per surrounding area.

Special Fire Fighting Procedures and Hazards: At temperatures above 60°C/140°F acid action on most metals may release hydrogen, a highly flammable and explosive gas.

5- REACTIVITY INFORMATION

Stable: Up to 110°C/230°F Unstable: Precautions: None Hazardous Polymerization Occurs: Does Not Occur: X

Incompatibility: Avoid contact with oxidizers. This material may be extremely hazardous in contact with

chlorates or nitrates. Contact with hypochlorites will generate heat.

Hazardous Decomposition Product: Thermal decomposition may yield oxides of carbon.

Hydrogen gas may be released upon contact with certain metals.

Transchem Pro Inc. MSDS No. HP-640 - March 01, 2014

6- HEALTH HAZARDS - PROTECTIVE MEASURES - FIRST AID

Inhalation:

- Can cause nose, throat and respiratory tract irritation.
- · Acute exposure is irritating.
- Prolonged exposure can cause respiratory tract problems.
- Avoid breathing vapor or mist.
- Remove to fresh air. If symptoms persist, seek medical attention.

Skin:

- Acute exposure is irritating.
- Non corrosive to skin.
- Use impervious, Butyl rubber, or natural rubber gloves.
- Wear full protective clothing. Take safety shower if necessary.
- Immediately flush with water for 15 minutes while removing contaminated clothing and shoes. Completely decontaminate clothing, shoes, and leather goods before reuse.

Eyes:

- Contact may be painful and irritating.
- Prolonged exposure can cause eye irritation problems.
- Wear chemical splash goggles or full face mask. Use eye bath if necessary.
- Immediately flush with water for 15 minutes. Call a doctor immediately

Ingestion:

- Product may be harmful or fatal if swallowed.
- Avoid swallowing. Wear face shield if face contact with concentrated product is likely.
- Rinse mouth. Do not induce vomiting. Drink large amounts of water. Get prompt medical attention.

IN ALL CASES: GET PROMPT MEDICAL ATTENTION IF EFFECTS PERSIST.

KEEP OUT OF REACH OF CHILDREN.

Most likely routes of entry: Skin, Eyes, Inhalation, Ingestion.

7- PRECAUTIONS FOR SAFE HANDLING AND USE

<u>Personal Protective Equipment:</u> Gloves: Use impervious gloves. Respiratory: Not normally required if good ventilation is maintained and exposure guidelines are not exceeded.

Eye: Chemical Splash goggles or full face mask. Other: Eye bath, safety shower, full protective clothing

<u>Spills and Leaks:</u> Before attempting clean-up, refer to hazard data given. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labelled containers. Prevent large spills from entering sewers or waterways. Contact emergency services and supplier for advice.

<u>Storage and Handling:</u> Use good housekeeping practices in storage. Store in a clean dry place. Keep containers closed. Store in plastic containers. DO NOT store in metal containers – especially aluminum. DO NOT store at temperatures above 120° F/49°C.

<u>Waste Disposal:</u> In accordance with applicable local, state, and federal regulations. This is not a RCRA hazardous waste as of this date.

Empty Containers: Rinse thoroughly before handling, reuse, disposal, or recycling.

8- REGULATORY INFORMATION

<u>DOT</u> (HM-181) USA: CORROSIVE LIQUID, Acidic, inorganic, N.O.S. (Phosphoric Acid), Class 8, UN 3264, PG III. [Int'l. (IMDG)]: CORROSIVE LIQUID, Acidic, inorganic, N.O.S. (Phosphoric Acid), Class 8, UN 3264, PG III.

SARA, Title III: Reportable for Section 313(Form R): Glycol Ether (Butyl Cellosolve), (5 -10%)

TSCA INVENTORY: All ingredients are commercially available and presumed to be listed by manufacturer.

CALIFORNIA PROP. 65: No listed substances are known to be present.

NEW JERSEY LABEL INGREDIENTS: Water (CAS# 7732-18-5), Phosphoric Acid (CAS# 7664-38-2),

Ethylene Glycol Butyl Ether (CAS# 111-76-2), Alcohol ethoxylate (CAS# 68439-46-3).

CANADA EPA DSL INVENTORY: Consult Transchem Pro Inc. regarding status of ingredients.

The information contained here in has been compiled from sources believed to be reliable and is accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Recipient assumes all responsibility for the use of this information and the use, storage, or disposal of the product, including any resultant personal injury or property damage.