



Transchem Pro Inc.  
745 McClintock, Ste 330  
Burr Ridge, IL 60527

# Technical Fact Sheet

## NAME:

UNSCENTED FRICTION DETERGENT (HP11)

## DESCRIPTION:

A high foaming hyper-concentrated detergent for use in all types of friction car wash equipment.

## BENEFITS:

Economical: A high foaming concentrate that yields between 2,500 and 5,000 cars per 5 gallon carboy.

Safe: Will not harm car finishes. It is especially formulated to not strip wax off of automobiles.

Lubricity: Unsurpassed in brush and soft-cloth lubrication. Helps protect car finishes from damage during washing.

Hard Water Compatible: Turtle Wax uses only hard water soluble and compatible surfactants. It is compatible with all types of water quality.

EcoLogo<sup>™</sup> Certified: In order to promote the use of more environmentally responsible products and services, the Environmental Choice<sup>™</sup> Program was established in 1988. The Environmental Choice<sup>™</sup> Program is Canada's only national and comprehensive eco-labeling program. The **EcoLogo<sup>™</sup>** is the recognized seal of approval of the Environmental Choice<sup>™</sup> Program.

## PACKAGING:

A 5-gallon plastic carboy.

## DILUTION:

Direct Feed: Apply 3/16 to 5/16 ounce (6-10 mL) of product per vehicle.

**NOTE:** Consult your local Turtle Wax distributor for complete information on the wide range of dilution options for this product. Actual dilution or chemical usage may vary based on desired results.

## SPECIFICATIONS:

Appearance:	A viscous, green liquid
Fragrance:	None
pH:	8.0
Density:	8.72 lbs/gal
Emulsifier:	Anionic
DOT Labeling:	None (Non-Hazardous)