

Technical Fact Sheet

NAME:

RUST INHIBITOR (HP35)

DESCRIPTION:

An undercarriage rust inhibitor for automatic car wash application.

BENEFITS:

Pre-Emulsified: This pre-emulsified formula is easy to dilute and simple to use.

Effective: It coats and protects the undercarriage of your car against harmful salt and road soils.

Economical: It extends economically in water and dilutes from 1:8 depending on desired level of protection.

EcoLogo^M Certified: In order to promote the use of more environmentally responsible products and services, the Environmental Choice^M Program was established in 1988. The Environmental Choice^M Program is Canada's only national and comprehensive eco-labeling program. The **EcoLogo^M** is the recognized seal of approval of the Environmental Choice^M Program.

PACKAGING:

A 5-gallon plastic carboy.

DILUTION:

Dilution Feed: Dilute product from 1:8 using a Hydro-minder or Omni Clean devise. Apply 1 to 3 ounces of diluted material through undercarriage arch.

Direct Feed: Apply 1/8 to 3/8 (3 to 11ml.) of concentrate per car by direct feed.

NOTE: Consult your local Turtle Wax distributor for complete information on the wide range of dilution options for this product. Actual dilution or chemical usage may vary based on desired results.

SPECIFICATIONS:

| | |
|---------------|-----------------------------------|
| Appearance: | Opaque Reddish-Orange Thin liquid |
| Fragrance: | None |
| pH: | Concentrate 10.0 Dilute 8.5 |
| Density: | 8.25 lbs/gal |
| Emulsifier: | Anionic |
| DOT Labeling: | None (Non-Hazardous) |