

# Technical Fact Sheet

**NAME:**

FOAMING PRESOAK (HP-76)

**DESCRIPTION:**

A CONCENTRATED high-foaming alkaline built formula for quick penetration and cleaning of grease and road soils. It is designed for use in self-serve car washes and as a pre-soak.

**BENEFITS:**

Fast Acting: A judicious blend of mild solvents and high foamers quickly solubilize and emulsify tough road grime and soils in even hard to clean areas.

High Foaming Formula: A thick rich lather helps lift the soil so that it is easily removed in the tunnel.

Hard water Compatible: Turtle Wax uses only hard water-soluble surfactants, it is compatible in all types of water quality.

Economical: It cleans up to 3200 cars per 5-gallon carboy when used as directed.

EcoLogo<sup>™</sup> Certified: In order to promote the use of more environmentally responsible products and services, the Environmental Choice<sup>™</sup> Program was established in 1988. The Environmental Choice<sup>™</sup> Program is Canada's only national and comprehensive eco-labeling program. The **EcoLogo<sup>™</sup>** is the recognized seal of approval of the Environmental Choice<sup>™</sup> Program.

**PACKAGING:**

A 5-gallon plastic carboy.

**DILUTION:**

Dilute Hyper-Concentrate at 1:472 - 1:378 and apply direct or apply 3.5 - 6 ml (1/8 - 1/5oz.) of Hyper-concentrate per cycle minute, OR dilute stock solution at 1:64 - 1:36 and apply 7.5 ounces per minute.

**NOTE:** To achieve these dilution rates, a special double tip assembly will be required. Contact your local Turtle Wax Distributor for more details. Actual dilution or chemical usage may vary based on desired results.

**SPECIFICATIONS:**

Appearance:	A thin fluorescent yellow liquid
Fragrance:	Citrus Lemon
pH:	14.0
Density:	9.47 lbs/gal
Emulsifier:	Anionic
DOT Labeling:	Corrosive (PG-II)